


## SPECIFICATION

- Part No. : **DSGP.1575.25.4.A.02**
- Description : GPS L1 / GALILEO E1 1575MHz 25\*25\*4mm  
Ceramic Patch SMT Antenna
- Features : 4.34 dBi Peak Gain for GPS/GALILEO Band  
Dims: 25\*25\*4mm  
SMT Direct Mount Ceramic Patch Antenna  
Automotive TS16949 Approved  
**RoHS compliant**



## 1. Introduction

The DSGP.1575.25.4.A.02 is a 25mm ceramic GPS L1 / GALILEO E1 passive patch antenna. 25mm square with a height of just 4mm, this antenna is perfect for applications in telematics devices, vehicle tracking/fleet management systems, and navigation devices. Typical applicable industries include transportation, defense, marine, agriculture, and navigation.

The antenna has been tuned on a 50\*50mm ground plane, working at 1575.42MHz with a 4.34dBi gain. The antenna has a stable hemispherical radiation pattern. The ceramic patch is mounted via SMT process, ideal for high volume, low cost assembly. It is manufactured and tested in a TS16949 first tier automotive approved facility.

For further optimization to customer specific device environments, custom tuned patch antennas can be supplied, subject to NRE and MOQ. For more details please contact your regional Taoglas sales office.


## 2. Specification

ELECTRICAL	
Application Bands	GPS/GALILEO
Operation Frequency	1575.42 ±1.023MHz
Return Loss	< -10dB
Gain at Zenith	4.34dBi
Efficiency	85.13%
Impedance	50Ω
MECHANICAL	
Ceramic Dimension	25*25*4mm
Weight	9.4g
ENVIRONMENTAL	
Operation Temperature	-40°C to 85°C
Humidity	Non-condensing 65°C 95% RH


\* Antenna properties were measured with the antenna mounted on 50\*50mm Ground Plane  
Taoglas Part # DSGPD.25A

## 3. Antenna Characteristics


### 3.1. Return Loss




### 3.2. Efficiency



### 3.3. Average Gain




### 3.4. Peak Gain






## 4. Antenna Radiation Pattern

### 4.1. Measurement Setup

The DSGP.1575.25.4 antenna is tested with 50\*50mm ground plane in a CTIA certified ETS-Lindgren Anechoic Chamber. The test setup is shown below.




## 4.2. 2D Radiation Pattern



### 4.3. 3D Radiation Pattern


1575.42MHz






## 5. Mechanical Drawing (Unit: mm)


Top View




Side View



Bottom View



## 6. Evaluation Board - DSGPD.25A (Unit: mm)




	Name	Material	Finish	QTY
1	PCB SMA(F) ST	Brass	Gold	1
2	DSGP.1575.25.4.A.02 Antenna	Ceramic	Clear	1
3	PCB (50x50x1mm)	FR4 1.0t	Black	1






## 7. PCB Footprint Recommendation

### 7.1. Footprint Copper Keepout Area (Unit: mm)

Pads 1, 2, 3, 4, 5, 6, 7 and 9 are the same size. They should be connected to GND.




**NOTE:**






- 1. Ag Plated area 
- 2. Solder Mask area 
- 3. Copper area 
- 4. Paste area 
- 5. Copper Keepout Area 
- 6. Copper keepout should extend through all PCB layers.
- 7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow.
- 8. The dimension tolerances should follow standard PCB manufacturing guidelines

## 7.2. Paste Area (Unit: mm)

Pads 1, 2, 3, 4, 5, 6, 7 and 9 are the same size.




**NOTE:**






- 1. Ag Plated area 
- 2. Solder Mask area 
- 3. Copper area 
- 4. Paste area 
- 5. Copper Keepout Area 
- 6. Copper keepout should extend through all PCB layers.
- 7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow.
- 8. The dimension tolerances should follow standard PCB manufacturing guidelines

### 7.3. Top Solder Mask (Unit: mm)


Pads 1, 2, 3, 4, 5, 6, 7 and 9 are the same size. This drawing is a negative of solder mask. Black regions are anti-mask.








**NOTE:**

- 1. Ag Plated area 
- 2. Solder Mask area 
- 3. Copper area 
- 4. Paste area 
- 5. Copper Keepout Area 
- 6. Copper keepout should extend through all PCB layers.
- 7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow.
- 8. The dimension tolerances should follow standard PCB manufacturing guidelines

## 7.4. Composite Diagram (Unit: mm)



**NOTE:**


- |                        |   |
|------------------------|---|
| 1. Ag Plated area      |  |
| 2. Solder Mask area    |  |
| 3. Copper area         |  |
| 4. Paste area          |  |
| 5. Copper Keepout Area |  |
6. Copper keepout should extend through all PCB layers.
  7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow.
  8. The dimension tolerances should follow standard PCB manufacturing guidelines

## 8. Recommended Reflow Soldering Profile

DSGP.25 can be soldered under a Lead-free process. According to the Standard IPC/JEDEC J-STD-020C, the temperature profile suggested is as follows:

Phase	Profile Features	Pb-Free Assembly (SnAgCu)
PREHEAT	Temperature Min( $T_{smin}$ ) Temperature Max( $T_{smax}$ ) Time( $t_s$ ) from ( $T_{smin}$ to $T_{smax}$ )	150°C 200°C 60-120 seconds
RAMP-UP	Avg. Ramp-up Rate ( $T_{smax}$ to $T_P$ )	3°C/second(max)
REFLOW	Temperature( $T_L$ ) Total Time above $T_L$ ( $t_L$ )	217°C 30-100 seconds
PEAK	Temperature( $T_P$ ) Time( $t_p$ )	260°C 2-5 seconds
RAMP-DOWN	Rate	3°C/second(max)
Time from 25°C to Peak Temperature		8 minutes max.
Composition of solder paste		96.5Sn/3Ag/0.5Cu
Solder Paste Model		SHENMAO PF606-P26

The graphic shows temperature profile for component assembly process in reflow ovens




Soldering Iron condition: Soldering iron temperature 270°C±10°C.

Apply preheating at 120°C for 2-3 minutes. Finish soldering for each terminal within 3 seconds, if soldering iron temperature over 270°C±10°C or 3 seconds, it will make cause component surface peeling or damage.


## 9. Packaging (Unit: mm)

200 pc DSGP1575.25.4.A.02 per reel  
 Dimensions -  $\varnothing 330 \times 55$ mm  
 Weight - 2330g







1 pc reel in small in Anti-static Bag  
Dimensions - 340\*350\*70mm  
Weight - 2.63Kg



4 Reels / 800 pcs in one carton  
Carton Dimensions - 370\*360\*305mm  
Weight - 11.3Kg



Pallet Dimensions 1200\*1000\*1420mm  
24 Cartons per Pallet  
6 Cartons per layer  
4 Layers



Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.