

TECHNICAL DATASHEET

2703A+ DIGITAL HOT AIR REWORK STATION





Product Description

All-in-one digital hot air station with soldering iron, de-soldering gun and built-in smoke absorber. Based on the popular 2702A+ but with dual ports so the soldering iron and desoldering gun can be used at the same time!

Key Features

- All digital controls
- Quick heat up
- Long life heating element
- Built-in air flow gauge
- 70 Watt soldering iron
- 500 Watt metal heater
- New heat tube with spreader for more even heat flow
- Automation feature that allows a 5 segment profile to be stored and run
- Digital calibration for the hot air, de-soldering gun and soldering iron.
- Programmable sleep timer for the hot air, desoldering gun and soldering iron.

Package Contents

- Main Unit with Attached Hot Air Gun
- Spare Hot Air Gun Heating Element
- Soldering Iron Handle with Smoke Absorber
- WQ-2B Soldering Tip
- 2663B Soldering Iron Stand
- B1003A De-Soldering Gun with 1.8mm Tip
- De-Soldering Gun Maintenance Kit with 1.0 and 1.5mm Tips
- Hot Air Nozzle Assortment (AT-12)
- Carbon Filter Pad
- Vacuum Suction Cap x 2
- 939 Vacuum Pen with 3 Suction Cups (Color Varies)
- IC Popper (2 Tips)
- Heat Resistant Pad
- Instruction Manual
- Power Cord









Specifications

Main Station

Input Voltage

110V

Temperature Scale

Digital °C

Station Dimensions

9.8 x 7.4 x 5" (250 x 188 x 126 mm)

Weight

12.4 Lbs (5.6 Kg)

Soldering Iron

Power Consumption

70W

Temperature Range

200 - 480°C (392 - 896°F)

Output Voltage

24V

Heating Element / Tip Type

WQ-Series

Hot Air Gun

Power Consumption

500W

Temperature Range

100 - 480°C (212 - 896°F)

Pump Type

Diaphragm Pump

Air Capacity

23 L / min (Max)

Heating Element

AO20094

Heat Tube

AO20962

De-Soldering Gun

Temperature Range

380 - 480°C (716 - 896°F)

Output Voltage

24V

Heating Element

AOC006A

Air Suction Flow

15 L/min (max)

Vacuum Generator

Vacuum Pump

Vacuum Pressure

600mm Hg



