

Readability **0.0001g (0.1 mg)**

- High contrast LCD screen.
- Large stainless steel pan.
- Below balance weighing
- Multiple weighing units (20 total).
- 3 Door anti-static draft shield.
- Leveling feet.
- RS 232 & USB interface.

► **Standard Functions**

- Weighing.
- Parts counting.
- Percentage weighing.
- Accumulation.
- Dynamic weighing.
- Density measurement.
- Peak hold - Accumulation.
- Weigh - Below function.

► **Accessories Included**

- 200 g calibration weight.
- Tweezers.
- RS-232 cable.
- Glove and bursh.

► **TECHNICAL DATA**

| Model                 | VE-204  | VE-210            |
|-----------------------|---|-------------------|
| Capacity              | 220 g   | 220 g.            |
| Readability           | 0.0001 g (0.1 mg)   | 0.0001g (0.1 mg). |
| Repeatability         | ±0.0001 g   | ±0.0001 g.        |
| Linearity             | ±0.000.2 g  | ±0.2 g.           |
| Weighing Units        | g, ct, oz, ozt, dwt, GN, lb, N, dr, tIT, tIs, tIH, T, T/A/R, /A/R, ms, bat, mom, /lb, kg. |                   |
| Calibration           | Internal  | External          |
| Pan Size              | Ø 90 mm / Ø 3.5".   |                   |
| Stabilization Time    | ≤ 3 seconds.  |                   |
| Interface             | RS-232 and USB included.  |                   |
| Display               | LCD, digit height 25mm / 1"   |                   |
| Housing               | Metal base and ABS plastic.   |                   |
| Operating Environment | 10° to 30°C / 50° to 85°F / Humidity 20% - 80%  |                   |
| Overall Dimensions    | 360 x 217 x 345 mm / 14.5" x 9" x 13.6".  |                   |
| Power Supply          | 110/240V, 50/60 AC Adapter.   |                   |
| Net Weight            | 7.5 kg/ 16.5lb  | 6.8 kg / 15 lbs   |
| Warranty              | 1 year.   |                   |