





- > Stainless steel offers corrosion resistance
- > 80% anti-magnetic (20% magnetic due to weld during manufacturing)
- > Pointed tips offer precise gripping of fine components
- > 92 27 61 and 92 27 62 are 1000V insulated
- > ESD handle versions discharge electrostatic energy through the handles in a gradual and controlled manner
- > 92 21 02 ESD and 92 28 72 ESD (Dissipative $10^4/10^9$ OHM regarding DIN EN 61340-5-1)




92 21 02 ESD, 92 22 04,
92 22 13 and 92 28 72 ESD





92 27 61 and 92 27 62



92 22 35



92 34 36



	Product Number	Length	Width	Height	Finish	Style	Gripping Surface	Tip (A)	Tip (B)
	92 21 02 ESD	5"	1/2"	1/2"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.30 mm	0.50 mm
	92 22 04	5"	1/2"	3/8"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.30 mm	0.50 mm
	92 22 13	5 1/8"	7/16"	9/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.40 mm	0.50 mm
	92 22 35	6"	5/16"	11/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	serrated	0.50 mm	0.50 mm
	92 27 61	5"	7/16"	1 3/8"	stainless steel, 80% anti-magnetic, acid resistant, 1000V VDE	straight	smooth	0.50 mm	0.50 mm
	92 27 62	6"	5/16"	1 9/16"	stainless steel, 80% anti-magnetic, acid resistant, 1000V VDE	straight	serrated	1.00 mm	1.30 mm
	92 28 72 ESD	5 1/8"	7/16"	9/16"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.40 mm	0.50 mm
	92 34 36	6"	5/16"	11/16"	stainless steel, 80% anti-magnetic, acid resistant	25° angled	serrated	0.50 mm	0.50 mm