







Dec.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		USB2.0 SPECIFICATION AND MICRO-USB CABLES AND CONNECTORS SPECIFICATION 			
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO +85° C 	STORAGE TEMPERATURE RANGE	-30 °C TO +85 °C 	
	VOLTAGE	-	OPERATING HUMIDITY RANGE	- % TO - %	
	CURRENT	-	APPLICABLE CABLE	-	
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING		CONFIRMED VISUALLY.		X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
	3	DIS-E-001673	TS. SAKAI ZAWA	KN. ICHIKAWA	07. 07. 24
REMARK			APPROVED	AO. SUZUKI	07. 03. 06
			CHECKED	HK. TANAKA	07. 03. 06
			DESIGNED	TS. SAKAI ZAWA	07. 03. 06
			DRAWN	TS. SAKAI ZAWA	07. 03. 06
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-126148-00	
	SPECIFICATION SHEET		PART NO.	ZX20-B-SLDC	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL242-0022-1-00	 1/1