

Specification Sheet

Part Number: PBM10C2



Push Mounts, when used with standard cable ties, provide a permanent bundling solution below a panel.

The "button" style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

Push-Button Cable Tie Mount, 0.25" Hole Dia, 0.12" Max Panel, 0.2" Max Tie Width, PA66, White, 100/pkg

Article Number 151-00230

Type PBM

Color White (WH)

Quantity Per bag

Product Description HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for installation below or underneath a panel. Designed for simple installation by pushing the mount through a pre-drilled hole. The low profile "button" style head is suitable in space constrained areas.

Short Description Push-Button Cable Tie Mount, 0.25" Hole Dia, 0.12" Max Panel, 0.2" Max Tie Width, PA66, White, 100/pkg

Global Part Name PBM-PA66-WH

Length L (Metric) 10.7

Width W (Imperial) 0.26

Width W (Metric) 6.6

Cable Ties T18 - T50

Height H (Imperial) .40

Height H (Metric) 10.20

Cable Tie Width Max (Imperial) 0.2

Cable Tie Width Max (Metric) 5.0

Panel Thickness Min (Imperial) 0.118

Panel Thickness Max (Imperial) 0.12

Panel Thickness Min (Metric) 3.0

Panel Thickness Max (Metric) 3.0

Mounting Hole Diameter D (Imperial) 0.25 - 0.29

Mounting Hole Diameter D (Metric) 6.25 - 6.55 mm

Mounting Hole Diameter D Min (Imperial) 0.25

Mounting Hole Diameter D Max (Imperial) 0.29

Mounting Hole Diameter D Max (Metric) 6.55

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL 94 V-2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988

