



Component Specification

C00911

**1.00mm PCB Sockets
October 2021**

SECTION	TITLE	PAGE
1	Description of Connector and Intended Application	2
2	Ratings	2

1. **DESCRIPTION OF COMPONENT AND INTENDED APPLICATION**

A range of sockets designed to interface components with Ø1.00mm pins to printed circuit boards, allowing a change of components when required.

2. **RATINGS**

2.1. **Electrical Characteristics**

Current Rating:	
In isolation, 25°C ambient	10.0A max
In isolation, 85°C ambient	7.5A max
Contact Resistance:	
Initial	10mΩ max
After Conditioning	25mΩ max

2.2. **Environmental Characteristics**

Environmental classification	55/125/21
Operating Temperature Range	-55°C to +125°C
Vibration Severity	10Hz to 2,000Hz, 0.75mm, 98m/s ² (10G), duration 6 hours

2.3. **Mechanical Characteristics**

Durability:	
Gold on contact area	1,000 operations
Tin on contact area	100 operations
High Temperature, Long Term (current as in 2.1.)	50 hours at 85°C
Clip Retention in Body	18N min
<i>Minimum retention force may be 18N from a sample of 10 sockets, providing the average of the samples is 27N.</i>	
Insertion Force (initial, with Ø1.00mm pin)	9.0N max
Withdrawal Force (initial, with Ø1.00mm pin)	1.0N min
Range of Mating Pin Diameter	Ø0.90mm to Ø1.05mm