



## Connectors 160/163

### 160 ST/ 4 DS NA

plug, 4 pole, wire protector (DS): yes, natural, voltage rating: 400 V, cross-section rating: 2.5 mm<sup>2</sup>



#### Order Info

|                            |               |
|----------------------------|---------------|
| reference number (ref.no.) | 150564        |
| PU                         | 500           |
| EAN                        | 4028012117581 |

#### Type

|                         |                     |
|-------------------------|---------------------|
| type                    | plug                |
| number of poles         | 4 pole              |
| clamping units per pole | 1                   |
| colour                  | natural             |
| cross-section rating    | 2.5 mm <sup>2</sup> |
| PE function             | yes                 |
| wire protector (DS)     | yes                 |

#### Technical Data

|                                    |                     |
|------------------------------------|---------------------|
| voltage rating                     | 400 V               |
| current rating                     | 16 A                |
| contact material                   | brass               |
| core cross-section min.            | 0.5 mm <sup>2</sup> |
| core cross-section max.            | 2.5 mm <sup>2</sup> |
| impulse voltage rating             | 4.0 kV              |
| flammability rating                | V-2                 |
| max. ambient temperature operation | 70 °C               |
| IP code                            | IP20                |
| IP code when plugged               | IP40                |
| type of conductor solid            | yes                 |
| type of conductor flexible         | yes                 |
| type of conductor stranded         | yes                 |
| stripping length                   | 6.5-7.0 mm          |