

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: 74004
Page 1 of 2 Pages

Issue: 3
Issue Date: 6/21/2018
Effective Date: 6/21/2018

A. Construction

Diameters (In)

- | | | | |
|----|---------------|---|-------|
| 1) | Component 1 | 4 X 1 PAIR | |
| | a) Conductor | 26 (7/34) AWG Bare Copper | 0.019 |
| | b) Insulation | 0.012" Wall, Nom. Polyethylene, Foam-Skin | 0.043 |
| | (1) Color(s) | | |

Pair	Color	Pair	Color	Pair	Color
1	WHITE - BLUE	3	WHITE - GREEN		
2	WHITE - ORANGE	4	WHITE - BROWN		

- | | | | |
|----|-----------------------|---|--------------------|
| c) | Pair | 2/Cond Cabled Together | |
| | (1) Twists: | Staggered Lays | |
| | Individually Applied: | | |
| | d) Shield: | Alum/Mylar Tape, 20% Overlap, Min. | |
| | (1) Foil Direction | Foil Facing Out | |
| 2) | Cable Assembly | 4 Components Cabled | |
| 3) | Shield | Tinned Copper BRAID Shield, 65% Coverage, Min. | |
| 4) | Jacket | 0.028" Wall, Nom., Polyurethane, Zero Halogen (ZH) | 0.268 (0.276 Max.) |
| | a) Color(s) | BLACK | |
| | b) Print | ALPHA WIRE-H P/N 74004 4PR 26 AWG
INDUSTRIAL ETHERNET SHIELDED ANSI/TIA-568-C.2
CAT7 VERIFIED FT2 CE ROHS (SEQ FOOTAGE) | |

B. Applicable Specifications

- | | | | |
|----|-------------------|--|----------------------------|
| 1) | UL | AWM/STYLE 21292 | 80°C / 30 V _{RMS} |
| 2) | CSA International | FT2 | |
| 3) | IEC | IEC 60811-2-1 Oil Resistance
IEC 60754-1 Halogen Free | |
| 4) | Other | ISO/IEC 11801 Category 7
EN 50173-1 | |
| 5) | CE: | EU Low Voltage Directive 2014/35/EC | |

C. Environmental Compliance

- | | | |
|----|----------------------------------|---|
| 1) | CE: | EU Directive 2011/65/EU(RoHS2):
This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C . |
| 2) | REACH Regulation (EC 1907/2006): | This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration . |

D. Physical & Mechanical Properties

- | | | |
|----|-------------------|--|
| 1) | Temperature Range | -40 to 80°C (static), -40 to 80°C (dynamic) |
| 2) | Bend Radius | 5X Cable Diameter(static), 10X Cable Diameter(dynamic) |
| 3) | Pull Tension | 18 Lbs, Maximum |

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: 74004
Page 2 of 2 Pages

Issue: 3
Issue Date: 6/21/2018
Effective Date: 6/21/2018

E. Electrical Properties

(For Engineering purposes only)

Max. operating voltage UL	300 V rms
Dielectric strength cond. – cond. (2 sec.)	2.5kVdc
D.C. resistance conductor	<145 Ω/km
Resistance unbalance	< 2%
D.C. insulation resistance	> 5000 MΩ.km
Mutual capacitance	< 56 nF/km
Capacitance unbalance	< 1600 pF/km
Velocity of propagation	≥ 70%
Skew @ 100 MHz	≤ 40 ns/100m
Propagation delay	≤ 534 + 36/√f ns/100m
Mean characteristic impedance (Zcm) @ 100 MHz	100 ± 5 Ω
Input impedance 1-600MHz	100 ± 15 Ω
Transfer Impedance (Z _T) @ 10 MHz	< 5 mOhm/m

Frequency (MHz)	Max. Insertion Loss (dB/100m)	Min. NEXT (dB)	Min. PS-NEXT (dB)	Min. ELFEXT (dB/100m)	Min. PS-ELFEXT (dB/100m)	Min. Return Loss (dB)
1	2.7	80	77			
4	5.5	80	77	58	55	23
10	8.5	80	77	50	47	25
16	10.8	80	77	46	43	25
20	12.1	80	77	44	41	25
31.25	15.2	80	77	40	37	23.6
62.5	27.8	75.1	72.1	34	31	21.5
100	27.8	72.4	69.4	30	27	20.1
200	40.1	67.9	64.9	24	21	18
300	50	65.3	62.3	20	17	17.3
600	73.3	60.8	57.8	14	11	17.3

F. Other

- 1) Packaging
 - a) 500 FT
- Flange (mm)
260 Continuous length
[Spool dimensions may vary slightly]

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.